

ROUTER + SW + VPN DrayTek Vigor 2915ac 2xWAN 16xVP



Cena :

1.218,70 zł (netto)

1.499,00 zł (brutto)

Nr katalogowy : **08873**

Stan magazynowy : **brak w magazynie**

Średnia ocena : **brak recenzji**

Router dla klientów biznesowych z obsługą do dwóch niezależnych sieci internetu , z obsługą szyfrowanych połączeń VPN , z funkcją rozdzielania ruchu przez sieć WiFi

Interface

| | |
|-------------------------|---|
| Fixed WAN Port | 1x 10/100/1000Base-TX, RJ-45 |
| WAN/LAN Switchable Port | 1x 10/100/1000Base-TX, RJ-45 (WAN 2 or LAN Port 4) |
| Fixed LAN Port | 3x 10/100/1000Base-TX, RJ-45 |
| USB Port | 1x USB 2.0 for 3G/4G/LTE USB modem, storage, printer or thermometer |
| Button | 1x Factory Reset Button 1x Wireless On/OFF/WPS Button (ac model) |
| 2.4G WLAN | 802.11n 2x2 MIMO 400 Mbps (ac model) |
| 5G WLAN | 802.11ac 2x2 MIMO 867 Mbps (ac model) |

Performance

| | |
|---|-------------------------|
| NAT Throughput | 500 Mbps |
| NAT Throughput w/ Hardware Acceleration | 900 Mbps |
| IPsec VPN Performance | 200 Mbps (AES 256 bits) |
| SSL VPN Performance | 150 Mbps |
| Max. Number of NAT Sessions | 30,000 |
| Max. Concurrent VPN Tunnels | 16 |
| Max. Concurrent OpenVPN + SSL VPN | 8 |

Internet Connection

| | |
|-----------------------------|--|
| IPv4 | PPPoE, DHCP, Static IP, PPTP/L2TP |
| IPv6 | PPP, DHCPv6, Static IP, TSPC, AICCU, 6rd, 6in4 Static Tunnel |
| 802.1p/q Multi-VLAN Tagging | |
| Multi-VLAN for Triple Play | |
| Wireless WAN | (ac model) |
| WAN Load Balancing | |
| WAN Failover | |
| WAN Active on Demand | Link Failure, Traffic Threshold |
| Connection Detection | ARP, Ping |
| WAN Data Budget | |
| Dynamic DNS | |
| DrayDDNS | |

LAN Management

| | |
|----------------------------|--|
| VLAN | 802.1q Tag-based, Port-based |
| Max. Number of VLAN | 8 |
| Number of LAN Subnet | 4 |
| DHCP Server | Multiple IP Subnet, Custom DHCP Options, Bind-IP-to-MAC |
| Port Mirroring | |
| Local DNS Server | |
| Conditional DNS Forwarding | |
| Hotspot Web Portal | |
| Hotspot Authentication | Click-Through, Social Login, SMS PIN, RADIUS, External Portal Server |

Networking

| | |
|-----------------------|--|
| Routing | IPv4 Static Routing, IPv6 Static Routing, Inter-VLAN Routing, RIPv1/v2 |
| Policy-based Routing | Protocol, IP Address, Port, Domain |
| DNS Security (DNSSEC) | |
| Multicast | IGMP Proxy v2/v3, IGMP Snooping, Bonjour |
| SMB File Sharing | (Requires external storage) |

VPN

| | |
|----------------------|--|
| LAN-to-LAN | |
| Teleworker-to-LAN | |
| Protocols | PPTP, L2TP, IPsec, L2TP over IPsec, SSL, GRE, IKEv2, IKEv2-EAP, IPsec-XAuth, OpenVPN |
| User Authentication | Local, RADIUS, LDAP, mOTP |
| IKE Authentication | Pre-Shared Key, X.509 |
| IPsec Authentication | SHA-1, SHA-256, MD5 |

Encryption MPPE, AES, DES, 3DES
VPN Trunk (Redundancy) Load Balancing, Failover
Single-Armed VPN
NAT-Traversal (NAT-T)

Firewall & Content Filtering

NAT Port Redirection, Port Triggering, DMZ Host, UPnP
ALG (Application Layer Gateway) SIP, RTSP, FTP, H.323
VPN Pass-Through PPTP, L2TP, IPsec
IP-based Firewall Policy
Content Filtering Application, URL, DNS Keyword, Web Features, Web Category* (*: subscription required)
DoS Attack Defense
Spoofing Defense

Bandwidth Management

IP-based Bandwidth Limit
IP-based Session Limit
QoS (Quality of Service) TOS, DSCP, 802.1p, IP Address, Port, Application
VoIP Prioritization
APP QoS

Wireless LAN (ac model)

Number of SSID 4 per band
Security Mode WEP, WPA, WPA2, Mixed(WPA+WPA2)
Authentication Pre-Shared Key, 802.1X
WPS PIN, PBC
WDS Bridge, Repeater (5G only)
Access Control Access List, Client Isolation, Hide SSID, Wi-Fi Scheduling
AirTime Fairness
Band Steering
WMM

Management

Local Service HTTP, HTTPS, Telnet, SSH, TR-069
Config File Export & Import
Config File Compatibility Vigor2912
Firmware Upgrade TFTP, HTTP, TR-069
2-Level Administration Privilege
Access Control Access List, Brute Force Protection
Notification Alert SMS, E-mail
SNMP v2, v2c, v3
Syslog
Managed by VigorACS

Physical

Power Supply DC 12V @ 2A
Max. Power Consumption 11.3 watts (ac model)
Dimension 220mm x 160mm x 36mm
Weight 400g (ac model)
Operating Temperature 0 to 45°C
Storage Temperature -25 to 70°C
Operating Humidity (non-condensing) 10 to 90%
