

ROUTER + SW + VPN DrayTek Vigor 2915ac 2xWAN 16xVP



Cena :

1.218,70 zł (netto)

1.499,00 zł (brutto)

Nr katalogowy : **08873**

Stan magazynowy : **brak w magazynie**

Średnia ocena : **brak recenzji**

Router dla klientów biznesowych z obsługą do dwóch niezależnych sieci internetu , z obsługą szyfrowanych połączeń VPN , z funkcją rozdzielania ruchu przez sieć WiFi

Interface

Fixed WAN Port	1x 10/100/1000Base-TX, RJ-45
WAN/LAN Switchable Port	1x 10/100/1000Base-TX, RJ-45 (WAN 2 or LAN Port 4)
Fixed LAN Port	3x 10/100/1000Base-TX, RJ-45
USB Port	1x USB 2.0 for 3G/4G/LTE USB modem, storage, printer or thermometer
Button	1x Factory Reset Button 1x Wireless On/OFF/WPS Button (ac model)
2.4G WLAN	802.11n 2x2 MIMO 400 Mbps (ac model)
5G WLAN	802.11ac 2x2 MIMO 867 Mbps (ac model)

Performance

NAT Throughput	500 Mbps
NAT Throughput w/ Hardware Acceleration	900 Mbps
IPsec VPN Performance	200 Mbps (AES 256 bits)
SSL VPN Performance	150 Mbps
Max. Number of NAT Sessions	30,000
Max. Concurrent VPN Tunnels	16
Max. Concurrent OpenVPN + SSL VPN	8

Internet Connection

IPv4	PPPoE, DHCP, Static IP, PPTP/L2TP
IPv6	PPP, DHCPv6, Static IP, TSPC, AICCU, 6rd, 6in4 Static Tunnel
802.1p/q Multi-VLAN Tagging	
Multi-VLAN for Triple Play	
Wireless WAN	(ac model)
WAN Load Balancing	
WAN Failover	
WAN Active on Demand	Link Failure, Traffic Threshold
Connection Detection	ARP, Ping
WAN Data Budget	
Dynamic DNS	
DrayDDNS	

LAN Management

VLAN	802.1q Tag-based, Port-based
Max. Number of VLAN	8
Number of LAN Subnet	4
DHCP Server	Multiple IP Subnet, Custom DHCP Options, Bind-IP-to-MAC
Port Mirroring	
Local DNS Server	
Conditional DNS Forwarding	
Hotspot Web Portal	
Hotspot Authentication	Click-Through, Social Login, SMS PIN, RADIUS, External Portal Server

Networking

Routing	IPv4 Static Routing, IPv6 Static Routing, Inter-VLAN Routing, RIPv1/v2
Policy-based Routing	Protocol, IP Address, Port, Domain
DNS Security (DNSSEC)	
Multicast	IGMP Proxy v2/v3, IGMP Snooping, Bonjour
SMB File Sharing	(Requires external storage)

VPN

LAN-to-LAN	
Teleworker-to-LAN	
Protocols	PPTP, L2TP, IPsec, L2TP over IPsec, SSL, GRE, IKEv2, IKEv2-EAP, IPsec-XAuth, OpenVPN
User Authentication	Local, RADIUS, LDAP, mOTP
IKE Authentication	Pre-Shared Key, X.509
IPsec Authentication	SHA-1, SHA-256, MD5

Encryption MPPE, AES, DES, 3DES
VPN Trunk (Redundancy) Load Balancing, Failover
Single-Armed VPN
NAT-Traversal (NAT-T)

Firewall & Content Filtering

NAT Port Redirection, Port Triggering, DMZ Host, UPnP
ALG (Application Layer Gateway) SIP, RTSP, FTP, H.323
VPN Pass-Through PPTP, L2TP, IPsec
IP-based Firewall Policy
Content Filtering Application, URL, DNS Keyword, Web Features, Web Category* (*: subscription required)
DoS Attack Defense
Spoofing Defense

Bandwidth Management

IP-based Bandwidth Limit
IP-based Session Limit
QoS (Quality of Service) TOS, DSCP, 802.1p, IP Address, Port, Application
VoIP Prioritization
APP QoS

Wireless LAN (ac model)

Number of SSID 4 per band
Security Mode WEP, WPA, WPA2, Mixed(WPA+WPA2)
Authentication Pre-Shared Key, 802.1X
WPS PIN, PBC
WDS Bridge, Repeater (5G only)
Access Control Access List, Client Isolation, Hide SSID, Wi-Fi Scheduling
AirTime Fairness
Band Steering
WMM

Management

Local Service HTTP, HTTPS, Telnet, SSH, TR-069
Config File Export & Import
Config File Compatibility Vigor2912
Firmware Upgrade TFTP, HTTP, TR-069
2-Level Administration Privilege
Access Control Access List, Brute Force Protection
Notification Alert SMS, E-mail
SNMP v2, v2c, v3
Syslog
Managed by VigorACS

Physical

Power Supply DC 12V @ 2A
Max. Power Consumption 11.3 watts (ac model)
Dimension 220mm x 160mm x 36mm
Weight 400g (ac model)
Operating Temperature 0 to 45°C
Storage Temperature -25 to 70°C
Operating Humidity (non-condensing) 10 to 90%
