

## ROUTER + SW + VPN DrayTek Vigor 2915 2xWAN 16xVPN



**Cena :**  
**974,80 zł (netto)**  
**1.199,00 zł (brutto)**

Nr katalogowy : **08874**  
 Stan magazynowy : **brak w magazynie**  
 Średnia ocena : **brak recenzji**

Router dla klientów biznesowych z obsługą do dwóch niezależnych sieci internetu , z obsługą szyfrowanych połączeń VPN

### Interface

Fixed WAN Port	1x 10/100/1000Base-TX, RJ-45
WAN/LAN Switchable Port	1x 10/100/1000Base-TX, RJ-45 (WAN 2 or LAN Port 4)
Fixed LAN Port	3x 10/100/1000Base-TX, RJ-45
USB Port	1x USB 2.0 for 3G/4G/LTE USB modem, storage, printer or thermometer
Button	1x Factory Reset Button
2.4G WLAN	802.11n 2x2 MIMO 400 Mbps (tylko model z rozszerzeniem ac)
5G WLAN	802.11ac 2x2 MIMO 867 Mbps (tylko model z rozszerzeniem ac)

### Performance

NAT Throughput	500 Mbps
NAT Throughput w/ Hardware Acceleration	900 Mbps
IPsec VPN Performance	200 Mbps (AES 256 bits)
SSL VPN Performance	150 Mbps
Max. Number of NAT Sessions	30,000
Max. Concurrent VPN Tunnels	16
Max. Concurrent OpenVPN + SSL VPN	8

### Internet Connection

IPv4	PPPoE, DHCP, Static IP, PPTP/L2TP
IPv6	PPP, DHCPv6, Static IP, TSPP, AICCU, 6rd, 6in4 Static Tunnel
802.1p/q Multi-VLAN Tagging	
Multi-VLAN for Triple Play	
Wireless WAN	(tylko model z rozszerzeniem ac)
WAN Load Balancing	
WAN Failover	
WAN Active on Demand	Link Failure, Traffic Threshold
Connection Detection	ARP, Ping
WAN Data Budget	
Dynamic DNS	
DrayDDNS	

### LAN Management

VLAN	802.1q Tag-based, Port-based
Max. Number of VLAN	8
Number of LAN Subnet	4
DHCP Server	Multiple IP Subnet, Custom DHCP Options, Bind-IP-to-MAC
Port Mirroring	
Local DNS Server	
Conditional DNS Forwarding	
Hotspot Web Portal	
Hotspot Authentication	Click-Through, Social Login, SMS PIN, RADIUS, External Portal Server

### Networking

Routing	IPv4 Static Routing, IPv6 Static Routing, Inter-VLAN Routing, RIPv1/v2
Policy-based Routing	Protocol, IP Address, Port, Domain
DNS Security (DNSSEC)	
Multicast	IGMP Proxy v2/v3, IGMP Snooping, Bonjour
SMB File Sharing	(Requires external storage)

### VPN

LAN-to-LAN	
Teleworker-to-LAN	
Protocols	PPTP, L2TP, IPsec, L2TP over IPsec, SSL, GRE, IKEv2, IKEv2-EAP, IPsec-XAuth, OpenVPN
User Authentication	Local, RADIUS, LDAP, mOTP
IKE Authentication	Pre-Shared Key, X.509

IPsec Authentication	SHA-1, SHA-256, MD5
Encryption	MPPE, AES, DES, 3DES
VPN Trunk (Redundancy)	Load Balancing, Failover
Single-Armed VPN	
NAT-Traversal (NAT-T)	

#### Firewall & Content Filtering

NAT	Port Redirection, Port Triggering, DMZ Host, UPnP
ALG (Application Layer Gateway)	SIP, RTSP, FTP, H.323
VPN Pass-Through	PPTP, L2TP, IPsec
IP-based Firewall Policy	
Content Filtering	Application, URL, DNS Keyword, Web Features, Web Category* (*: subscription required)
DoS Attack Defense	
Spoofing Defense	

#### Bandwidth Management

IP-based Bandwidth Limit	
IP-based Session Limit	
QoS (Quality of Service)	TOS, DSCP, 802.1p, IP Address, Port, Application
VoIP Prioritization	
APP QoS	

#### Wireless LAN ( tylko model z rozszerzeniem ac )

Number of SSID	4 per band
Security Mode	WEP, WPA, WPA2, Mixed(WPA+WPA2)
Authentication	Pre-Shared Key, 802.1X
WPS	PIN, PBC
WDS	Bridge, Repeater (5G only)
Access Control	Access List, Client Isolation, Hide SSID, Wi-Fi Scheduling
AirTime Fairness	
Band Steering	
WMM	

#### Management

Local Service	HTTP, HTTPS, Telnet, SSH, TR-069
Config File Export & Import	
Config File Compatibility	Vigor2912
Firmware Upgrade	TFTP, HTTP, TR-069
2-Level Administration Privilege	
Access Control	Access List, Brute Force Protection
Notification Alert	SMS, E-mail
SNMP	v2, v2c, v3
Syslog	
Managed by VigorACS	

#### Physical

Power Supply	DC 12V @ 2A
Max. Power Consumption	11.3 watts (tylko model z rozszerzeniem ac)
Dimension	220mm x 160mm x 36mm
Weight	400g (tylko model z rozszerzeniem ac)
Operating Temperature	0 to 45°C
Storage Temperature	-25 to 70°C
Operating Humidity (non-condensing)	10 to 90%