Utworzono 04-11-2026

ROUTER + SW + VPN DrayTek Vigor 2136ax 1xWAN 2xVPN



Cena :
893,50 zł (netto)
1.099,01 zł (brutto)
Nr katalogowy : **09386**
Stan magazynowy : **brak w magazynie**
Średnia ocena : **brak recenzji**

Router dla klientów biznesowych z obsługą jednej sieci internetu oraz sieci zapasowej na USB , z obsługą szyfrowanych połączeń VPN , z funkcją rozdzielenia ruchu przez sieć WiFi , z obsługą 2,5 Gb LAN oraz WiFi ax

1x WAN | 4 podsieci | 16 VPN | 50 tys. sesji

- **WAN 2.5 Gigabit Ethernet** z wydajnością NAT do 2.3 Gbps
- Dwuzakresowe **Wi-Fi 6 (AX3000)** z prędkością 2402Mbps dla 5GHz oraz 574Mbps dla 2.4GHz
- WAN Failover
- 16 równoczesnych tuneli VPN IPsec/WireGuard/OpenVPN
- Wydajność IPsec do 300 Mbps
- Firewall SPI z filtrowaniem treści według słów kluczowych URL, kategorii stron, aplikacji
- USB do podłączenia modemu 3G/4G, dodatkowej pamięci, termometru, drukarki
- Centralne zarządzanie VigorAP
- Bezpłatna usługa DrayDDNS z certyfikatem Let's Encrypt
- System DrayOS 5
- DEMO WebUI – seria Vigor 2136

Model	Vigor2136	Vigor2136ax
Performance		
NAT Session	50K	
Max. NAT (Mbps)	2300	
WAN		
Ethernet (2.5 GbE)	2	
Ethernet - LAN/WAN Switchable		
Cellular (via USB)	2	
Wireless WAN (2.4GHz + 5GHz)		
Internet Connection		
IPv4	PPPoE DHCP Static IP	
IPv6	PPP DHCPv6 Static IPv6 TSPC 6rd 6in4 Static Tunnel	
802.1p/q Multi-VLAN Tagging		
Failover		
Connection Detection	ARP, Ping	
WAN Data Budget		
Dynamic DNS		
DrayDDNS		
LAN		
Fixed LAN (RJ-45, GbE)	3	
LAN Subnet	4	
VLAN	802.1q Tag-based VLAN	
Max. Number of VLAN	8	
DHCP Server	Multiple IP Subnet Custom DHCP Options Bind-IP-to-MAC	
Wired 802.1x Authentication		
Port Mirroring		
Local DNS Server		
Conditional DNS Forwarding		
Hotspot Web Portal (Profile No.)	2	

multicomp

Hotspot Authentication	Click-Through Social Login SMS PIN RADIUS External Portal Server
WLAN	
2.4GHz WLAN	802.11ax 2x2 MIMO
5GHz WLAN	802.11ax 3x3 MU-MIMO
WiFi Antenna (External)	2
WiFi Antenna (Internal)	1
2.4GHz Antenna Gain (dBi)	2.6
5GHz Antenna Gain (dBi)	2.7
2.4GHz Max. Link Rate (Mbps)	574
5GHz Max. Link Rate (Mbps)	2402
Max. Number of SSIDs (per band)	8 (4)
Security Mode	OWE WEP WPA WPA2 WPA2/WPA WPA3 WPA3/WPA2
Authentication	Pre-Shared Key, 802.1X
WiFi 6	
OFDMA	
Roaming	Assisted Roaming
WPS	WPS Button, PIN Code
WDS	Repeater
Access Control	Access List Client Isolation Hide SSID WLAN Scheduling
AirTime Fairness	
Band Steering	
WMM	
Mesh (5GHz Only)	Root
Other Ports	
USB	2
USB Type	2.0
USB Application	User Management FTP File Sharing Device Status Printer Server Temperature Sensor USB WAN File Explorer
SMB File Sharing (Requires external storage)	
Networking	
Routing	IPv4 Static Route IPv6 Static Route Policy Route Inter-VLAN Route RIP v1/v2 OSPF(V2/V3) BGP
Policy-based Routing	Protocol IP Address Port
DNS Security (DNSSEC)	
IGMP	IGMP v2/v3 IGMP Proxy IGMP Snooping & Fast Leave
Local RADIUS server	
Bandwidth Management	
Traffic Shaping Policy	
IP-based Bandwidth Limit	
IP-based Session Limit	
QoS (Quality of Service)	IP Address Port Application
APP QoS	
Default Policy	
VoIP Prioritization	
NAT	
Port Forwarding	

multicomp

DMZ Host	
Port Trigger	
ALG (Application Layer Gateway)	SIP, RTSP, FTP, H.323
UPnP	
Management	
Local Service	HTTP HTTPS Telnet SSH v2 FTP TR-069
Config Backup/Restore	
Firmware Upgrade	WUI, TFTP, TR-069
Role-based Privilege	
Access Control	Access List, Brute Force Protection
Notification Alert	SMS, E-mail
SNMP	v1, v2c, v3
Syslog	
Virtual AP Controller (Device up to)	20
Mesh (Number of manageable APs)	7
Virtual Switch Controller	5
VigorACS Management (Since f/w)	V5.3.0
Security	
URL/IP Reputation	
Firewall Filter	IP, Content, Traffic
Port Knocking	
Defense Setup	ARP Spoofing, IP Spoofing
MAC Filtering Profile	
IPv6 Address Security	
IAM	
Users & Groups	
Access Policies	
Group Policies	
Conditional Access Policy	
Resources	
Account Status	
Backup and Restore	
VPN	
Site-to-Site VPN	
Teleworker VPN	
EasyVPN	
Protocols	IPsec IKEv1/IKEv2 IKEv2-EAP IPsec-XAuth OpenVPN WireGuard
Max. VPN Tunnels	16
IPsec VPN Throughput (AES 256 bits) (single-directional) (Mbps)	390
WireGuard VPN Throughput (single-directional) (Mbps)	90
User Authentication	Local RADIUS TACACS+ mOTP TOTP
IKE Authentication	Pre-Shared Key, X.509
IPsec Authentication	SHA-1, SHA-256
Encryption	DES 3DES AES
Single-Armed VPN	
NAT-Traversal (NAT-T)	
VPN Connection Status	
Backup & Restore	
Monitoring	
Clients List	
Log Center	
Wireless Information	
WAN	
ARP Table	
Route Table	
DHCP Table	
IPv6 TSPC Status	
IPv6 Neighbor Table	
LLDP Neighbors	

multicomp

DNS Cache Table		
Remote DSL Status		
PPPoE Pass-Through		
Session Table		
Running Table		
Physical		
Power Input	DC 12V @ 0.9A	DC 12V @ 1.5A
Max. Power Consumption (watts)	10	18
Dimension (mm)	207 x 131 x 42	
Operating Temperature	0 to 45°C	
Storage Temperature	-25 to 70°C	
Operating Humidity (non-condensing)	10 to 90%	

https://www.draytek.com/products/router-matrix

multicomp